

Specifications

MATERIALS

COMPONENTS	ALLOY	YIELD STRENGTH	STANDARD COLORS
Aluminum Extrusion Rails	6005-T5	35,000 PSI	BLK, WH, BRZ
Stainless Steel screws painted to match fence color			
Components Coated	TGIC Polyester Powder Coating Technology TGIC provides twice the thickness and hardness TGIC provides fade and scratch resistance		

DIMENSIONS

COMPONENTS	RESIDENTIAL	COMMERCIAL	INDUSTRIAL **
Pickets	5/8" sq. x .045" Thick	3/4" sq. x .050" Thick	1" sq x .060" Thick
Rails Topwalls	1-1/8" x .060" Thick	1-3/8" x .065" Thick	1-7/8" x .090" Thick
Sidewalls	1" x .075" Thick	1-1/4" x .088" Thick	1-5/8" x .100" Thick
Posts	2" sq. x .060" Thick	2"sq. x .125" Thick	2-1/2" sq. x .100" Thick
	2" sq. x .075" Thick	2"sq. x .075" Thick	3" sq. x .125" Thick
Gate Posts	2-1/2" sq. x .100" Thick	2-1/2" sq. x .100" Thick	3" sq. x .125" Thick
	2" sq. x .125" Thick	3" sq. x .125" Thick	4" sq. x .125" Thick
		4" sq. x .125" Thick	
Picket Spacing	3-13/16"	3-5/8"	3 15/16"
	1-5/8" (also available)	1-1/2" (also available)	1-1/2" (also available)
Post Spacing ***	72-1/2" on center	99-5/8" on center	70-5/8" on center
		72-1/2" (also available)	95 5/16" (also available)
Section Heights	36", 48", 54", 57", 60", 72"	36", 48", 54", 57", 60", 72"	36", 48", 60", 72", 84", 96"
Standard Gate Openings	36", 48", 60", 72"	36", 48", 60", 72"	36", 48", 60", 72"

All Gates Welded

*Customized Sizes Available

**Please Call Office for Lead Time

***Residential Based on 2" Post. Commercial & Industrial Based on 2-1/2" Post



OnGuard Ornamental Aluminum Fence
Manufacturer
355 New Albany Road Moorestown, NJ 08057
Phone: (866) 321-0001, (908) 429-5522
Fax: 908-429-9933
<https://www.ogfence.com>

Sales Manager:

Darryl Hurd | 908-546-0795 | darryl@ogfence.com

Sales Executives:

Vinny Cirrito | 845-269-2622 | vinny@ogfence.com

Fran Duffy | 609-439-1185 | fran@ogfence.com

Customer Service:

cs1@ogfence.com